

XP0121G IP Phone

6 Line HD SIP desktop phone with liquid crystal display (LCD)

The Xorcom XP Series of IP phones provides high definition (HD) sound quality and a comprehensive range of traditional business and VoIP features to the enterprise desktop. The Xorcom XP0121G is an advanced **6-line HD SIP phone** with a graphic LCD (Liquid Crystal Display), designed for maximum productivity and efficiency in the everyday business environment.



General	
Chipset	Broadcom
Flash memory	128MB
SRAM memory	64MB
Dimensions (W*D*H*T; handset on cradle, stand attached)	230mm x 222mm x 170mm x 55mm
Weight (handset on cradle, stand attached)	
Temperature	-10~50° C
Humidity	10-95%
Power consumption(approx.)	0.98 ~ 3.87W
Connections	
LAN (PC port)	10/100/1000Mbps Ethernet
WAN (Internet port)	10/100/1000Mbps Ethernet
Adapter	Input : AC 100-240V Output : DC 5V/2A
PoE(802.3af) built-in	√
PoE(802.3af) class	Class 2
Handset(RJ-9)	√
Headset(RJ-9)	√
Foot stand	√
Wall mounting	√
Expansion module	6

User interface	
Display type	3.66" 240×120 graphic LCD
LCD Backlight	√
Hard keys in all	39
DSS keys	21
Soft keys	4
Navigation keys	6
Volume key	√
Fixed feature keys	8 (Menu/Message/Headset/Hold/ Mute/Tran/Redial/Handsfree)
Power and ring indicator LED	√
DSS keys with dual color LED	√
Message indicator LED	√
Headset indicator LED	√
External device	
XP0020 Expansion module	√
EHS36 wireless headset adapter	√
YHS32 headset	√
Voice	
HD voice	HD Speaker HD Handset
Wideband codec	G.722
G.711 A-law/μ-law	√
G.726	√
G.723.1	x
G.729AB	√
HAC (Hearing aid compatibility)	√
VAD (Voice activity detection)	√
CNG (Comfort noise generator)	√
AEC (Acoustic echo canceling)	√
PLC (Packet loss concealment)	√

AJB (Adaptive jitter buffer)	√
AGC (Automatic gain control)	√
Side tone	√
Quality of Service(QoS)	802.1p/Q, ToS/DSCP
Telephony features	
SIP Accounts	6
Hands-free speakerphone	Full Duplex
Redial	√
Auto redial	√
Mute	√
3-way conferencing	√
Caller ID display	√
Call hold	√
Call waiting	√
Call transfer(blind/attended)	√
Call forward	√
Call History(all/missed/ received/dialed/forwarded)	100 entries
DND	√
SMS	√
Voice mail	√
Message waiting indicator(MWI)	√
Speed Dial	√
Ringtone selection	√
Volume control	√
Import of individual ringtone	√
Tone setting	√
Local Phonebook	1000 entries
Phonebook import/export	√
Phonebook search	Intelligent search method
Black list	√
Phone lock (keypad lock)	√

LCD display logo	✓
# or * key as Send function	✓
Hotline	✓
Localized language	✓
Reset to factory	✓
View Voice Mail	✓
Headset (Call center mode)	✓
Zero-SP-Touch	✓
IP PBX and IP Centrex features	
BLF (Busy Lamp field)	✓
BLA(Bridged Line Appearance)	✓
Paging	✓
Intercom	✓
Call park	✓
Call pickup	✓
Call completion	✓
Call recording	✓
Anonymous call	✓
Anonymous call rejection	✓
Auto answer	✓
Emergency call	✓
Call return	✓
Group pickup	✓
Group listening	✓
Distinctive Ringtone	✓
Music on hold(via PBX)	✓
Music on hold(via sever)	✓
Dial Plan	✓
PUSH XML	✓

Network and Time	
WAN Static IP/DHCP/PPPoE	√
PC port mode	Bridge
DHCP server for PC port	√
SNTP/NTP	√
Setup date and time by manual	√
Daylight saving time	√
IPv6	ICMPv6, Static
DNS Cache	√
VLAN	Autoconfiguration through DHCP/LLDP
Action URL& Action URI	√
Multicast IP Paging	√
Security	
HTTPS (server/client)	√
TLS (Transport Layer Security)	√
S RTP (RFC3711)	√
AES for auto-provision	√
3-level privilege	Admin/VAR/User
Web Interface	
Embedded web server	HTTP/HTTPS
Edit phonebook via web	√
Send SMS via web	√
Dial via web	√
Web logout	√
Management (config/upgrade)	
Configuration via LCD	√
Configuration via web	√
Configuration via autoprovision	√
Automatic firmware update	√
Manual firmware update	√
Auto provisioning via LCD	√

Auto provisioning via Web	TFTP/FTP/HTTP/HTTPS
Auto provisioning with PnP	✓
TR-069	✓
Redundancy Server	✓
SNMP	✓
Provisioning redirection (via phone)	✓
Package tracing export	✓
System log export	✓
SIP	
SIP v1 (RFC2543)	✓
SIP v2 (RFC3261)	✓
UDP/TCP/TLS	✓
Out-of-band DTMF(RFC 2833)	✓
In-band DTMF	✓
SIP INFO DTMF	✓
STUN client (NAT traversal)	✓
Rport (RFC3581)	✓
Digest/basic authentication	Digest (MD5)
Peer-to-peer SIP link mode	✓
Loose routing and strict routing support	✓
PRACK (RFC3262)	✓
Error-information support	✓
Reliability of provisional responses (RFC3262)	✓
DNS SRV (RFC3263), redundant server support	✓
Offer/answer (RFC3264)	✓
Message Waiting Indication (RFC3842)	✓
Subscription for MWI events (RFC3265)	✓
Dialog-state monitoring(RFC 4235)	✓
REFER (RFC3515)	✓
Event list subscription support (RFC4662)	✓
Advanced features	

XML phonebook (Central)	√
XML browser	√
Hot-desking	√
OpenVPN	√
802.1x	√
LDAP phonebook	√
Soft key programmable	√
Broadsoft Advanced Features	
Network Conference	√
Network Call Logs	√
Auto-P synchronization	√
DND & Forward synchronization	√
BLF List	√
Call Forward	√
Call Pickup	√
Call Park	√
Call Center Features	√
Contacts	Custom/Enterprise/Personal/ Common/Search/Speed Dial
Meet-me conference	√
Alert-Info	√
BroadWorks Anywhere	√
Sequential Ring	√
Simultaneous Ring Personal	√
Anonymous Call	√
Anonymous Call Rejection	√
Remote Office	√

CosmoCom Advanced Features	
ACD	√
Other features	
Certification	CE/FCC
Broadsoft Validated	√
Asterisk/Digium Certificated	√
Packing	
Giftbox size	250mm x 255mm x 132mm
PCS/CTN	5 PCS
Carton measure	680mm x 260mm x 267mm
N.W	
G.W	